

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Patent Abstracts of Japan

PUBLICATION NUMBER : JP5216550
 PUBLICATION DATE : 27-08-93
 APPLICATION NUMBER : JP920264549
 APPLICATION DATE : 02-10-92


VOL: 17 NO: 658 (P - 1654)
 AB. DATE : 06-12-1993 PAT: A 5216550
 PATENTEE : MATSUSHITA ELECTRIC IND CO
 LTD
 PATENT DATE: 27-08-1993

INVENTOR : IKEDA MASAHARU


INT.CL. : G05F3/20; H02J1/00

TITLE : VOLTAGE GENERATOR


(a)



(b)



(c)



ABSTRACT : PURPOSE: To obtain a voltage independent of the temperature even under a supply voltage lower than a specific voltage (1.25V).
 CONSTITUTION: This voltage generator is provided with an output terminal 1, current sources 11 and 15, and a transistor TR 12 subjected to diode connection. A current is allowed to flow from the current source 15 to resistances 13 and 14 connected in series to obtain the voltage of the output terminal 1. Current sources 11 and 15 are band gap current sources. When the current source 15 is made open, the part of the TR 12 is expressed by an equivalent circuit 120 using a voltage source 121 and a resistance 122, and the equivalent circuit 120 and resistances 13 and 14 are expressed by the equivalent circuit 130 by using the Ohtori-Thevenin's theorem.